

• DESCRIPTION

Polyprime WB is a water based bitumen primer designed for a variety of applications as a primer and sealer coat.

• FEATURES

- Economical.
- Waterproof and weatherproof.
- Anti Corrosive.
- Non Toxic.
- Easy to apply.

• USES

Polyprime WB is used as a primer coat prior to application of torch applied bituminous waterproofing membranes and oxidized bitumen. **Polyprime WB** is resistant to alkalis and acids and can withstand prolonged oxidation.

• APPLICATION INSTRUCTIONS

Surface Preparation

Ensure that all surfaces that are to be treated are sound and free from oil, grease, cement laitance and loosely adhering particles. If required, light mechanical grinding or wire brushing is recommended.

Application

The surface must be dry before priming with **Polyprime WB**. Thoroughly mix the contents of the drum so that there is no settlement due to storage. Apply the product by brush or roller at an average coverage rate of 2-4 m²/ lt./coat. For dry and porous surfaces apply a second coat. The second coat is to be applied only after the first coat dries completely. The primer should be allowed to dry naturally before the application of subsequent layers.

• TECHNICAL DATA

Flash point	Non flammable
Tack free time	6 hours at 30°C
Color	Brown/Black
Density	1 g/cc
Coverage	2-4 m ² / lt./coat
Firm Set	24 hours
Application temperature	+5°C to +45°C

- **PACKING**

20 lt. pails and 200 lt. drums.

- **STORAGE AND SHELF LIFE**

Store under cover, out of direct sunlight and protect from extreme temperature. Shelf life is up to 12 months when stored as above. Failure to comply with the recommended storage conditions may result in premature deterioration of the product.

- **HEALTH AND SAFETY**

As with all bitumen products caution should always be exercised. Protective clothing such as gloves and goggles should be worn. (See packaging for specific instructions) Treat any splashes to the skin or eyes with fresh water immediately. Should any of the products be accidentally swallowed, do not induce vomiting. Call for medical assistance immediately. Ensure that the container is available for medical attendant to examine any relevant instructions and contents details.

Last revised May 2008



The information given in this data sheet is based on our current knowledge of the product when properly stored, handled and applied. We cannot guarantee that the product will be suitable, effective or safe when used for any purpose other than its stated uses.
To the extent that it is lawful, we exclude warranties implied by law and limit our liability to the cost of replacing the product. We accept no responsibility for loss or injury caused by improper use, incompetent preparation, inexpert or negligent application, or ordinary wear and tear.
Service or advice given by our staff should not amount to responsibility for the project - since the owner, or their contractor is responsible for procedures relating to the application of the product.

Distributed by



A Division of River Sands Pty Ltd

683 Beenleigh-Redland Bay Rd, Carbrook, Qld 4130 > Ph (07) 3287 6444 > Fax (07) 3287 6445
Sydney > Ph (02) 9677 1056 > Fax (02) 9677 1352
Melbourne > Ph (03) 9311 9225 > Fax (03) 9311 9445
Perth > Ph 0423 023 164
Toll Free > 1800 077 744 > Email acs@riversands.com.au > www.appliedconcretesolutions.com.au