

ACS GROUT FEATURES

CONSTANT PERFORMANCE

Features (click on product name for more information)	Construction Grout	Grout GP	Grout HES30	Grout HF30	Grout TC	Grout UW
High Strength	✓	✓	✓	✓		✓
Medium Strength					✓	
Non Shrink/Shrink Compensated	✓	✓	✓	✓		
Rapid Setting			✓			
Pumpable/Pourable		✓	✓	✓	✓	✓
Rammable	✓	✓			✓	
Injectable				✓		
Free Flowing			✓	✓	✓	✓
Initial High Flow			✓	✓	✓	✓
High Flow				✓		
Vibration Resistant			✓	✓	✓	
Impact Resistant			✓	✓		
Thermal Variation Resistant			✓	✓		
Compression Resistant			✓		✓	
Non Corrosive (Chloride Free)				✓	✓	✓
Underwater Applications						✓
Geothermal Applications					✓	

CONSTANT PERFORMANCE

For further information consult the Material Safety Data Sheet and read the product label carefully before use. Material Safety Data Sheets are available by phoning 1800 077 744.

PLEASE NOTE
 The information given in this sheet is based on our current knowledge of the product when properly stored, handled and applied. We cannot guarantee that the product will be suitable, effective or safe when used for any purpose other than its stated uses.
 To the extent that it is lawful, we exclude warranties implied by law and limit our liability to the cost of replacing the product. We accept no responsibility for loss or injury caused by improper use, incompetent preparation, inexpert or negligent application, or ordinary wear and tear.
 Service or advice given by our staff should not amount to responsibility for the project - since the owner, or their contractor (and not River Sands), is responsible for procedures relating to the application of the product.

APPLIED CONCRETE SOLUTIONS
 A Division of River Sands Pty Ltd
 Corner Riverland and Monte-Khoury Drive,
 Loganholme QLD 4129, Australia
 Brisbane: (07) 3412 8111
 Sydney: (02) 9677 1056
 Melbourne: (03) 9311 9225
 Perth: 0423 023 164
 Toll Free Helpline: 1800 077 744
www.appliedconcretesolutions.com.au